




### Load Cell

Fig.	Thread	Part Number	Used With	Range
A	Male 1/8" NPT Threaded End 	DPG-3M45	<b>Micro 45<sup>®</sup> / Micro 70<sup>®</sup> Load Cell</b> (LC-045 / 90.300.045)	Force: 0-90 daN (0-200 lb.)
B		DPG-3M90	<b>Micro 90<sup>®</sup> Load Cell</b> (LC-090 / 90.300.090)	Force: 0-100 daN (0-200 lb.)
C		DPG-3M180	<b>Micro 180<sup>®</sup> Load Cell</b> (LC-180 / 90.300.180)	Force: 0-250 daN (0-500 lb.)
D		DPG-3M250	<b>Micro 250<sup>®</sup> Load Cell</b> (LC-250 / 90.300.250)	Force: 0-320 daN (0-700 lb.)
E		DPG-3U175	<b>U.0175 Load Cell</b> (LC-175 / 90.300.0175)	Force: 0-250 daN (0-500 lb.)
F		DPG-3U325	<b>U.0325 Load Cell</b> (LC-325 / 90.300.0325)	Force: 0-350 daN (0-750 lb.)
G		DPG-3LC	<b>Mini, Ultra Force<sup>®</sup>, Compact &amp; Large Gas Springs</b> (LC-0300 – LC-0750 / 90.300.0300 – 90.300.10000)	10-250 bar (100-3500 psi)



### Control Panel

Fig.	Thread	Part Number	Used With	Range
H	9/16-18 Female Threaded End 	DPG-3RB	<b>Convertible Control Panel</b> (90.406.P_)	0-450 bar (0-6000 psi)
J		DPG-3RM	<b>Convertible Control Panel</b> (90.406.A_)	0-450 bar (0-45 MPa)
K		DPG-3ML	<b>Common Control Panel</b> (90.416.A2B), <b>Control Panel with Pressure Monitor</b> (90.406.421), <b>Pressure Monitor</b> (90.416.A3N_)	0-450 bar (0-45 MPa)
L		DPG-3RL	<b>Mini Control Panel</b> (90.407.11G), <b>Compact Control Panel</b> (90.405.P_), <b>Mini Convertible Control Panel</b> (90.407P_)	0-450 bar (0-6000 psi)
M	Male 1/8" NPT Threaded End 	DPG-3R	<b>Multi Panel</b> (90.401.3) and <b>Pressure Analyzers</b> (DPA-5 / 90.315.5, DPA-4 / 90.315.4, DPA-3 / 90.315.3 and DPA-2 / 90.315.2)	0-450 bar (0-6000 psi)

Liquid filled gauges

