

DADCO's RT – Ratcheting Tool facilitates installation and removal of Dadco's Micro Series Threaded Body Style Nitrogen Gas Springs and Dadco's SL.16 and E.16 Nitrogen Gas Stock Lifters. The RT-50 Tool is available with a variety of internal and external hex drives to suit each threaded body model.



**RT-50-C1-C2**

**12 mm Bits**

**13 mm Bits**

**C1**



Hex Drive: 9.5 mm External; Hardened Steel  
 Fits Springs: **C.045.TB2 and TB4, SL.16\***  
 Max Torque: 200 lb-in (22 N-m)  
 Bit Size: 12 mm  
**Bit Part Number: RTB-C1**

**C2**



Hex Drive: 16 mm External; Hardened Steel  
 Fits Springs: **C.090.TB1 and TB2**  
 Max Torque: 400 lb-in (45 N-m)  
 Bit Size: 13 mm  
**Bit Part Number: RTB-C2**

**C1**



Hex Drive: 9.5 mm External, Hardened Steel  
 Fits Springs: **C.045.TB1**  
 Max Torque: 125 lb-in (14 N-m)  
 Bit Size: 12 mm  
**Bit Part Number: RTB-C1**

**C3**



Hex Drive: 17 mm Internal; Steel  
 Fits Springs: **C.045.TB3**  
 Max Torque: 200 lb-in (22 N-m)  
 Bit Size: 13 mm  
**Bit Part Number: RTB-C3**

**E1**



Hex Drive: 10 mm External; Steel  
 Fits Springs: **E.16.TB2, TB4, TB5**  
 Max Torque: 200 lb-in (22 N-m)  
 Bit Size: 12 mm  
**Bit Part Number: RTB-E1**

**S2**



Hex Drive: 12 mm Internal; Steel  
 Fits Springs: **SL.16\*\***  
 Max Torque: 200 lb-in (22 N-m)  
 Bit Size: 13 mm  
**Bit Part Number: RTB-S2**

**S1**



Hex Drive: 9.5 mm External; Brass  
 Fits Springs: **SL.16\*\***  
 Max Torque: 80 lb-in (9 N-m)  
 Bit Size: 12 mm  
**Bit Part Number: RTB-S1**

\*For springs that ONLY have 9.5 mm internal hex.

\*\*For springs with both 9.5 mm internal and 12 mm external hex. For reference only.

**Ordering Example:**

